



Bellavista™ 6 WHIRLPOOL BATH

- EE20 Bellavista™ 6 Whirlpool Bath with RapidHeat™ Right Hand
- BT65 Bellavista™ 6 Whirlpool Bath with RapidHeat™ Left Hand
- DB05 Bellavista™ 6 Whirlpool Bath with RapidHeat™ Right Front
- DB11 Bellavista™ 6 Whirlpool Bath with RapidHeat™ Right Back

Bellavista™ 6 SOAKER BATH

- Y870 Bellavista™ 6 Bath

- Center Drain Location
- Accessories / Hardware:
 - PowerPro™ Jet Rings: #M952
 - AccuPro™ Neck Jet Rings Kit: #P556 (3 Required)
 - SCH 40 Rotary Drain Kit: #DA34
 - Rotary Drain Kit, 30" Cable: #K606
- Trim Kit Finishes Available:
 - (827) – Chrome
 - (898) – Brushed Chrome
 - (815) – Satin Nickel
 - (829) – Bright Brass
 - (805) – Platinum
 - (826) – Brushed Nickel
 - (845) – Oil Rubbed Bronze

INSTALLATION NOTES

Refer to installation instructions included with fixture before beginning installation. Please confirm product availability and specifications before commencing with any installation work.

PRODUCT SPECIFICATIONS AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Technical Specifications

DIMENSIONS

72" L x 42" W x 26" H
(1829 mm) L x (1067 mm) W x (660 mm) H

DRAIN/OVERFLOW

A: 20" (508 mm) B: 11-3/4" (298 mm)

CUTOUT

Template Provided P/N P187000

TOTAL WEIGHT

EE20: 1180 lb (535 kg) / 56 lb/sq. ft. (273kg/m²)
Y870: 1150 lb (522 kg) / 55 lb/sq. ft. (268 kg/m²)

OPERATING GALLONAGE

87 U.S. Gal. (341 Liters)
Min. 75 U.S. Gal. (276 Liters)
Max. 98 U.S. Gal. (371 Liters)

PRODUCT WEIGHT

EE20: 130 lb (59 kg)
Y870: 100 lb (33 kg)

SKIRT MOUNTING

Not Available

ELECTRICAL SPECIFICATIONS – Model EE20 only

Requires a dedicated GFCI protected separate circuit.

Motor/Pump: 120 VAC, 20 AMP, 60 Hz.
RapidHeat™: 120 VAC, 15 AMP, 60 Hz.

HEATER (STANDARD) – Model EE20 only

Requires a dedicated GFCI protected separate circuit.

RapidHeat™: P/N S750000

